


31410 DIGHT LED 18W-NW

LED dustproof lighting fitting

8595665314101



GENERAL DATA:

Colour: grey

Place of assembly: ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Possibility of fixture-loop-through connection: yes

Compatible with a dimmer: no

Length [mm]: 600

Width [mm]: 64

Height [mm]: 60

Number of chokes: 2

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 18

Class of protection against electric shock: II

Lampshade material: PC

Diode type: LED SMD

Luminous flux [lm]: 1800

Useful luminous flux of the light source Φ_{use} [lm]: 2150

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80

Service life [h]: 20000

Number of on/off cycles: ≥ 25000

Lighting angle [°]: 110

Luminous efficiency of the lamp [lm/W]: 100

Ambient temperature range to which the product can be exposed: -20÷40

Enclosure material: plastic

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

IP class: 65

LOGISTIC DATA:

Unit of measurement: unit

31410 DIGHT LED 18W-NW

LED dustproof lighting fitting

Packaging method: 12
Number of units in the secondary packaging : 1
Number of units in the packaging : 12
Net unit weight [g] : 450
Grammage [g] : 586.67
Length of a unit pack [cm] : 63.5
Width of a unit pack [cm] : 6.5
Height of a unit pack [cm] : 6.5
Weight of a cardboard box [kg] : 7.04004
Width of a cardboard box [cm] : 29
Height of a cardboard box [cm] : 22.5
Length of a cardboard box [cm] : 65
Volume of a cardboard box [m³] : 0.042413